Modular signalling devices / LED modules

PL208

PIPS module single flash/quintuple flash/random clear / green

Green | Clear Iens | PIPS | Ø92mm | AC/DC



Specifications

Brand	PIPS
CE certificate	Yes
Certificates, quality marks, markings	CE, UL type 4X, EAC
Colour lens	Clear
Dimensions	Ø92mm x 107,5mm
Ingress protection	IP66
LED life	100 000h
LEDs colour	Green
Light pattern	Flashing

Light patterns	Blinking and flashing
Light source	LED
Luminous intensity	400cd
Operating temperature	-30°C to +50°C
Particularities	Blinks ± 110x1/minute, flashes ± 72x5/minute or in a random pattern
Rated current	12V AC/DC 450mA / 24V AC/DC 700mA / 40V AC/DC 800mA / 80V AC/DC 250mA / 120V AC 150mA / 240V AC 60mA
UL certificate	Yes
Voltage	Depending on the installed base
Weight	200g

Good to know 1



This module has a very high luminous intensity due to the use of 2x SuperBright LEDs, with inner Fresnel lens. The combination of the bright lens with 24 coloured Bright LEDs ensures a clear distinction between the ON and OFF status of this module even in bright surroundings. With the multi-channel technology you can easily switch the different light effects externally.

