

PL301

Blinking/permanent | LED light module | RGB/opal lens

EAN: 5414184702448



Specifications

Brand	PIPS	Luminous intensity	3cd
CE certificate	Yes	Operating temperature	-30°C to +50°C
Certificates, quality marks, markings	CE, UL type 4X, EAC	Particularities	Blinks ± 120x1/minute or ± 36x2/minute and flashes ± 60x4/minute or in a random pattern
Colour lens	Diffuse	Rated current	12V AC/DC 310mA / 24V AC/DC 180mA / 40V AC/DC 150A / 80V AC/DC 85mA / 120V AC 65mA / 240V AC 55mA
Dimensions	Ø92mm x 42,5mm	UL certificate	Yes
Ingress protection	IP66	Voltage	Depending on the installed base
LED life	100 000h	Weight	90g
LEDs colour	Multicolor		
Light patterns	Steady, blinking and rotating		
Light source	LED		

Good to know

Deze module heeft een multi-channel-technologie waarbij je 3 alarmniveaus volledig zelf kunt samenstellen. Kies uit maar liefst 8 kleuren en 5 lichteffecten. Bovendien kan je met deze technologie de verschillende niveaus eenvoudig extern omschakelen. PL301 is voorzien van een opale lens voor korte-afstandssignalisatie.