Signalling devices / Sirens & horns

A112NDC24 G

Electronic multitone siren, max. 119dB @ 1m, 10-30V DC, grey



Specifications

| Alarm stages | 4 |
|---|---------------------------------------|
| Brand | E2S |
| CE certificate | Yes |
| Cable entry | -40°C to +60°C |
| Certificates, quality marks, markings | CE, UL, cUL, Gost-R, EAC |
| Colour | RAL 7038 grey |
| Dimensions | 168mm x 168mm x 190mm |
| | |
| EN 54-3 | Yes |
| EN 54-3 Effective range | Yes 214m @ 1KHz |
| 2.10.0 | |
| Effective range | 214m @ 1KHz |
| Effective range Ingress protection | 214m @ 1KHz IP66 |
| Effective range Ingress protection Material | 214m @ 1KHz IP66 ABS Outside mounting |

| Operating voltage | 10-30V DC |
|------------------------|---|
| Range | 214m |
| Rated voltage | 24V DC |
| Relative humidity | Less than 90% (no condensation) at 20°C |
| Sound level (max) | 120dB(A) |
| | |
| Type | Electronic multitone siren |
| Type UL certificate | 2.000.01.101.101.101.10 |
| | siren |
| UL certificate | Yes |
| UL certificate Voltage | siren Yes 24V |

Good to know 1



It's possible to create 4 messages of 30s.