

SF08-
M1KTB-Y

Multi-function LED beacon | Ø80mm | 12-24V DC | terminal block | buzzer | yellow



Specifications

Brand	Patlite	Operating temperature	-20°C to +50°C
Buzzer	Yes	Operating voltage	10-30V DC
CE certificate	Yes	Particularities	Rotates 60x, 120x and 180x/minute or flashes 60x, 90x and 120x/minute or pulses 20x/minute
Cable length	500mm	Rated current	12V DC 0,64A / 24V DC 0,34A
Certificates, quality marks, markings	CE, cULus, EAC, KC	Rated voltage	12-24V DC
Colour lens	Yellow	Relative humidity	Less than 90% (no condensation) at 20°C
Dimensions	Ø80mm x 126mm	Sound level (max)	86dB
Impact resistance	4,5G	Type	Pre-configured
Ingress protection	IP66	UL certificate	Yes
LED life	100 000h	Voltage	12V DC / 24V DC
Light patterns	Rotating, flashing, pulsing, dimming and omni- or unidirectional	Weight	250g
Luminous intensity	800cd		
Material	Polycarbonate		
Mounting and connection type	-30°C to +80°C		

Good to know

This multifunctional LED beacon has 22 light patterns, divided into 10 groups with 4 levels each, from which to choose. You can easily configure the light pattern by adjusting the rotary switch and closing or opening the contacts externally. A good application example is adjusting the rotation speed depending on the degree of danger.

