

SF08-  
M2KTN-R

## Multi-function LED beacon, IP66, Ø80mm 100-240V AC, terminal block/red



### Specifications

|                                       |  |                              |  |
|---------------------------------------|--|------------------------------|--|
| Brand                                 | Patlite  | Material                     | Polycarbonate  |
| Buzzer                                | No   | Mounting and connection type | -30°C to +80°C   |
| CE certificate                        | Yes  | Operating temperature        | -20°C to +50°C   |
| Cable length                          | 500mm  | Operating voltage            | 90-250V AC   |
| Certificates, quality marks, markings | CE, cULus, EAC, KC   | Particularities              | Rotates 60x, 120x and 180x/minute or flashes 60x, 90x and 120x/minute or pulses 20x/minute |
| Colour lens                           | Red  | Rated current                | 100V AC 0,19A / 240V AC 0,08A  |
| Dimensions                            | Ø80mm x 120mm  | Rated voltage                | 100-240V AC (50/60Hz)  |
| Impact resistance                     | 4,5G   | Relative humidity            | Less than 90% (no condensation) at 20°C  |
| Ingress protection                    | IP66   | UL certificate               | Yes  |
| LED life                              | 100 000h   | Voltage                      | 115V AC / 230V AC  |
| Light patterns                        | Rotating, flashing, pulsing, dimming and omni- or unidirectional | Weight                       | 270g   |
| Luminous intensity                    | 650cd  |                              |  |

### Good to know i

This multifunctional LED beacon has 22 light patterns, divided into 10 groups with 4 levels each, from which to choose. You can easily configure the light pattern by adjusting the rotary switch and closing or opening the contacts externally. A good application example is adjusting the rotation speed depending on the degree of danger.

