

SF10-M1JN-
Y

Multi-function LED beacon, IP23, Ø100mm 12-24V DC, cable/yellow



Specifications

Brand	Patlite	Material	Polycarbonate
Buzzer	No	Mounting and connection type	3-screw mounting/cable
CE certificate	Yes	Operating temperature	-20°C to +50°C
Cable length	500mm	Operating voltage	10-30V DC
Certificates, quality marks, markings	CE, cULus, EAC, KC	Particularities	Rotates 60x, 120x and 180x/minute or flashes 60x, 90x and 120x/minute or pulses 20x/minute
Colour lens	Yellow	Rated current	12V DC 0,62A / 24V DC 0,32A
Dimensions	Ø100mm x 141mm	Rated voltage	12-24V DC
Impact resistance	4,5G	Relative humidity	Less than 90% (no condensation) at 20°C
Ingress protection	IP23 / IP65 with rubber gasket	UL certificate	Yes
LED life	100 000h	Voltage	12V DC / 24V DC
Light patterns	Rotating, flashing, pulsing, dimming and omni- or unidirectional	Weight	400g
Luminous intensity	1100cd		

Good to know i

This multifunctional LED beacon has 22 light patterns, divided into 10 groups with 4 levels each, from which to choose. You can easily configure the light pattern by adjusting the rotary switch and closing or opening the contacts externally. A good application example is adjusting the rotation speed depending on the degree of danger.

