

SF10-
M2KTN-G

Multi-function LED beacon, IP66, Ø100mm 100-240V AC, terminal block/green



Specifications

| | | | |
|---------------------------------------|--|------------------------------|--|
| Brand | Patlite | Material | Polycarbonate |
| Buzzer | No | Mounting and connection type | -30°C to +80°C |
| CE certificate | Yes | Operating temperature | -20°C to +50°C |
| Cable length | 500mm | Operating voltage | 90-250V AC |
| Certificates, quality marks, markings | CE, cULus, EAC, KC | Particularities | Rotates 60x, 120x and 180x/minute or flashes 60x, 90x and 120x/minute or pulses 20x/minute |
| Colour lens | Green | Rated current | 100V AC 0,19A / 240V AC 0,08A |
| Dimensions | Ø100mm x 140mm | Rated voltage | 100-240V AC (50/60Hz) |
| Impact resistance | 4,5G | Relative humidity | Less than 90% (no condensation) at 20°C |
| Ingress protection | IP66 | UL certificate | Yes |
| LED life | 100 000h | Voltage | 115V AC / 230V AC |
| Light patterns | Rotating, flashing, pulsing, dimming and omni- or unidirectional | Weight | 420g |
| Luminous intensity | 750cd | | |

Good to know i

This multifunctional LED beacon has 22 light patterns, divided into 10 groups with 4 levels each, from which to choose. You can easily configure the light pattern by adjusting the rotary switch and closing or opening the contacts externally. A good application example is adjusting the rotation speed depending on the degree of danger.

