

SF10-
M2KTN-R

Multi-function LED beacon, IP66, Ø100mm 100-240V AC, terminal block/red



Specifications

Brand	Patlite	Material	Polycarbonate
Buzzer	No	Mounting and connection type	-30°C to +80°C
CE certificate	Yes	Operating temperature	-20°C to +50°C
Cable length	500mm	Operating voltage	90-250V AC
Certificates, quality marks, markings	CE, cULus, EAC, KC	Particularities	Rotates 60x, 120x and 180x/minute or flashes 60x, 90x and 120x/minute or pulses 20x/minute
Colour lens	Red	Rated current	100V AC 0,19A / 240V AC 0,08A
Dimensions	Ø100mm x 140mm	Rated voltage	100-240V AC (50/60Hz)
Impact resistance	4,5G	Relative humidity	Less than 90% (no condensation) at 20°C
Ingress protection	IP66	UL certificate	Yes
LED life	100 000h	Voltage	115V AC / 230V AC
Light patterns	Rotating, flashing, pulsing, dimming and omni- or unidirectional	Weight	420g
Luminous intensity	750cd		

Good to know i

This multifunctional LED beacon has 22 light patterns, divided into 10 groups with 4 levels each, from which to choose. You can easily configure the light pattern by adjusting the rotary switch and closing or opening the contacts externally. A good application example is adjusting the rotation speed depending on the degree of danger.

