

**SKH-M2TB-  
R**

**LED rotation beacon | Ø100mm | 100-240V  
AC | terminal block | buzzer | red**



## Specifications

|                                       |                                 |                       |                                         |
|---------------------------------------|---------------------------------|-----------------------|-----------------------------------------|
| Brand                                 | Patlite                         | Operating temperature | -10°C to +50°C                          |
| Buzzer                                | Yes                             | Operating voltage     | 90-250V AC                              |
| CE certificate                        | Yes                             | Particularities       | Rotates<br>120x/minute                  |
| Cable length                          | 500mm                           | Rated current         | 100V AC 0,08A /<br>240V AC 0,05A        |
| Certificates, quality marks, markings | CE, cULus, EAC, KC              | Rated voltage         | 100-240V AC<br>(50/60Hz)                |
| Colour lens                           | Red                             | Relative humidity     | Less than 90% (no condensation) at 20°C |
| Dimensions                            | Ø100mm x 147mm                  | Sound level (max)     | 88dB                                    |
| Impact resistance                     | 4,5G                            | Type                  | Pre-configured                          |
| Ingress protection                    | IP23 / IP65 with rubber gasket  | UL certificate        | Yes                                     |
| LED life                              | 100 000h                        | Voltage               | 115V AC / 230V AC                       |
| Light patterns                        | Rotating                        | Weight                | 340g                                    |
| Luminous intensity                    | 5500cd                          |                       |                                         |
| Material                              | Polycarbonate                   |                       |                                         |
| Mounting and connection type          | 3-screw mounting/terminal block |                       |                                         |

