

**SKS-M2J-R**

## LED rotation beacon, IP23, Ø80mm 100-240V AC, cable/red



### Specifications

|                                       |                                |                              |   |
|---------------------------------------|--------------------------------|------------------------------|---|
| Brand                                 | Patlite                        | Material                     | Polycarbonate                           |
| Buzzer                                | No                             | Mounting and connection type | 3-screw mounting/cable                  |
| CE certificate                        | Yes                            | Operating temperature        | -10°C to +50°C                          |
| Cable length                          | 500mm                          | Operating voltage            | 90-250V AC                              |
| Certificates, quality marks, markings | CE, cULus, EAC, KC             | Particularities              | Rotates 120x/minute                     |
| Colour lens                           | Red                            | Rated current                | 100V AC 0,07A / 240V AC 0,04A           |
| Dimensions                            | Ø80mm x 121mm                  | Rated voltage                | 100-240V AC (50/60Hz)                   |
| Impact resistance                     | 4,5G                           | Relative humidity            | Less than 90% (no condensation) at 20°C |
| Ingress protection                    | IP23 / IP65 with rubber gasket | UL certificate               | Yes                                     |
| LED life                              | 100 000h                       | Voltage                      | 115V AC / 230V AC                       |
| Light patterns                        | Rotating                       | Weight                       | 270g                                    |
| Luminous intensity                    | 5300cd                         |                              |   |

