

**SL10-M2JN-
B**

LED steady/flash beacon, IP23, Ø100mm 100-240V AC, cable/blue



Specifications

| | | | |
|---------------------------------------|-----------------------------------|------------------------------|---|
| Brand | Patlite | Material | Polycarbonate |
| Buzzer | No | Mounting and connection type | 3-screw mounting/cable |
| CE certificate | Yes | Operating temperature | -20°C to +50°C |
| Cable length | 500mm | Operating voltage | 90-250V AC |
| Certificates, quality marks, markings | CE, cULus, EAC, KC | Particularities | Blinks 180x/minute or flashes 120x/minute |
| Colour lens | Blue | Rated current | 100V AC 0,08A / 240V AC 0,04A |
| Dimensions | Ø100mm x 141mm | Rated voltage | 100-240V AC (50/60Hz) |
| Impact resistance | 4,5G | Relative humidity | Less than 90% (no condensation) at 20°C |
| Ingress protection | IP23 / IP65 with rubber gasket | UL certificate | Yes |
| LED life | 100 000h | Voltage | 115V AC / 230V AC |
| Light patterns | Steady, blinking and triple flash | Weight | 400g |
| Luminous intensity | 45cd | | |

Good to know

Standard light functions with flash settings typify this LED beacon. The newly developed Fresnel lens distributes uniform light from all surfaces of the dome, including the top.

