

SL10-M2JN-  
G

LED beacon | Ø100mm | 100-240V AC |  
cable | green

EAN: 4938766023628



## Specifications

|                                       |                                   |                              |   |
|---------------------------------------|-----------------------------------|------------------------------|---|
| Brand                                 | Patlite                           | Material                     | Polycarbonate                             |
| Buzzer                                | No                                | Mounting and connection type | 3-screw mounting/cable                    |
| CE certificate                        | Yes                               | Operating temperature        | -20°C to +50°C                            |
| Cable length                          | 500mm                             | Operating voltage            | 90-250V AC                                |
| Certificates, quality marks, markings | CE, cULus, EAC, KC                | Particularities              | Blinks 180x/minute or flashes 120x/minute |
| Colour lens                           | Green                             | Rated current                | 100V AC 0,08A / 240V AC 0,04A             |
| Dimensions                            | Ø100mm x 141mm                    | Rated voltage                | 100-240V AC (50/60Hz)                     |
| Impact resistance                     | 4,5G                              | Relative humidity            | Less than 90% (no condensation) at 20°C   |
| Ingress protection                    | IP23 / IP65 with rubber gasket    | Type                         | Pre-configured                            |
| LED life                              | 100 000h                          | UL certificate               | Yes                                       |
| Light patterns                        | Steady, blinking and triple flash | Voltage                      | 115V AC / 230V AC                         |
| Luminous intensity                    | 80cd                              | Weight                       | 400g                                      |

## Good to know i

Standard light functions with flash settings typify this LED beacon. The newly developed Fresnel lens distributes uniform light from all surfaces of the dome, including the top.

