

SL10-M2JN-  
Y

LED beacon | steady/flash | IP23 | Ø100mm  
| 100-240V AC | cable | yellow



## Specifications

Brand	Patlite	Material	Polycarbonate
Buzzer	No	Mounting and connection type	3-screw mounting/cable
CE certificate	Yes	Operating temperature	-20°C to +50°C
Cable length	500mm	Operating voltage	90-250V AC
Certificates, quality marks, markings	CE, cULus, EAC, KC	Particularities	Blinks 180x/minute or flashes 120x/minute
Colour lens	Yellow	Rated current	100V AC 0,08A / 240V AC 0,04A
Dimensions	Ø100mm x 141mm	Rated voltage	100-240V AC (50/60Hz)
Impact resistance	4,5G	Relative humidity	Less than 90% (no condensation) at 20°C
Ingress protection	IP23 / IP65 with rubber gasket	Type	Pre-configured
LED life	100 000h	UL certificate	Yes
Light patterns	Steady, blinking and triple flash	Voltage	115V AC / 230V AC
Luminous intensity	100cd	Weight	400g

## Good to know ⓘ

Standard light functions with flash settings typify this LED beacon. The newly developed Fresnel lens distributes uniform light from all surfaces of the dome, including the top.

