

SL10-
M2KTB-B

LED beacon | steady/flash | IP66 | Ø100mm
| 100-240V AC | terminal block | buzzer |
blue



Specifications

Brand	Patlite	Operating temperature	-20°C to +50°C
Buzzer	Yes	Operating voltage	90-250V AC
CE certificate	Yes	Particularities	Blinks 180x/minute or flashes 120x/minute
Cable length	500mm	Rated current	100V AC 0,09A / 240V AC 0,05A
Certificates, quality marks, markings	CE, cULus, EAC, KC	Rated voltage	100-240V AC (50/60Hz)
Colour lens	Blue	Relative humidity	Less than 90% (no condensation) at 20°C
Dimensions	Ø100mm x 146mm	Sound level (max)	88dB
Impact resistance	4,5G	Type	Pre-configured
Ingress protection	IP66	UL certificate	Yes
LED life	100 000h	Voltage	115V AC / 230V AC
Light patterns	Steady, blinking and triple flash	Weight	400g
Luminous intensity	45cd		
Material	Polycarbonate		
Mounting and connection type	-30°C to +80°C		

Good to know ⓘ

Standard light functions with flash settings typify this LED beacon. The newly developed Fresnel lens distributes uniform light from all surfaces of the dome, including the top.

■ SL10-M1KTB/SL10-M2KTB



(Models with Buzzer Only)