

SL15-
M2KTN-G

LED steady/flash beacon, IP66, Ø150mm 100-240V AC, terminal block/green



Specifications

| | | | |
|---------------------------------------|-----------------------------------|------------------------------|---|
| Brand | Patlite | Material | Polycarbonate |
| Buzzer | No | Mounting and connection type | 3-point hole mounting/terminal block |
| CE certificate | Yes | Operating temperature | -20°C to +50°C |
| Cable length | 500mm | Operating voltage | 90-250V AC |
| Certificates, quality marks, markings | CE, cULus, EAC, KC | Particularities | Blinks 180x/minute or flashes 120x/minute |
| Colour lens | Green | Rated current | 100V AC 0,14A / 240V AC 0,06A |
| Dimensions | Ø150mm x 201mm | Rated voltage | 100-240V AC (50/60Hz) |
| Impact resistance | 4,5G | Relative humidity | Less than 90% (no condensation) at 20°C |
| Ingress protection | IP66 | UL certificate | Yes |
| LED life | 100 000h | Voltage | 115V AC / 230V AC |
| Light patterns | Steady, blinking and triple flash | Weight | 890g |
| Luminous intensity | 180cd | | |

Good to know i

Standard light functions with flash settings typify this LED beacon. The newly developed Fresnel lens distributes uniform light from all surfaces of the dome, including the top.

