

SL15-  
M2KTN-Y

LED beacon | Ø150mm | 100-240V AC |  
terminal block | yellow

EAN: 4938766023888



## Specifications

Brand	Patlite	Mounting and connection type	3-point hole mounting/terminal block
Buzzer	No	Operating temperature	-20°C to +50°C
CE certificate	Yes	Operating voltage	90-250V AC
Cable length	500mm	Particularities	Blinks 180x/minute or flashes 120x/minute
Certificates, quality marks, markings	CE, cULus, EAC, KC	Rated current	100V AC 0,14A / 240V AC 0,06A
Colour lens	Yellow	Rated voltage	100-240V AC (50/60Hz)
Dimensions	Ø150mm x 201mm	Relative humidity	Less than 90% (no condensation) at 20°C
Housing colour	Grey	Type	Pre-configured
Impact resistance	4,5G	UL certificate	Yes
Ingress protection	IP66	Voltage	115V AC / 230V AC
LED life	100 000h	Weight	890g
Light patterns	Steady, blinking and triple flash		
Luminous intensity	220cd		
Material	Polycarbonate		

## Good to know

Standard light functions with flash settings typify this LED beacon. The newly developed Fresnel lens distributes uniform light from all surfaces of the dome, including the top.

