

SL15-
M2KTN-Y

LED beacon | IP66 | Ø150mm | 100-240V AC
| terminal block | yellow

EAN: 4938766023888



Specifications

Brand	Patlite	Mounting and connection type	3-point hole mounting/terminal block
Buzzer	No	Operating temperature	-20°C to +50°C
CE certificate	Yes	Operating voltage	90-250V AC
Cable length	500mm	Particularities	Blinks 180x/minute or flashes 120x/minute
Certificates, quality marks, markings	CE, cULus, EAC, KC	Rated current	100V AC 0,14A / 240V AC 0,06A
Colour lens	Yellow	Rated voltage	100-240V AC (50/60Hz)
Dimensions	Ø150mm x 201mm	Relative humidity	Less than 90% (no condensation) at 20°C
Housing colour	Grey	Type	Pre-configured
Impact resistance	4,5G	UL certificate	Yes
Ingress protection	IP66	Voltage	115V AC / 230V AC
LED life	100 000h	Weight	890g
Light patterns	Steady, blinking and triple flash		
Luminous intensity	220cd		
Material	Polycarbonate		

Good to know

Standard light functions with flash settings typify this LED beacon. The newly developed Fresnel lens distributes uniform light from all surfaces of the dome, including the top.

