

LR6-02WCNW

Base unit LR6 | M30 mount | M12 | Ø60mm | off-white



Specifications

Brand	Patlite	Mounting direction	Upright
Connection	Direct mount/M12 connectors	Operating temperature	-20°C to +50°C
Dimensions	Ø60mm	Pole mounting	No
Housing colour	Off-white	Rated voltage	24V DC
Ingress protection	IP65	Relative humidity	Less than 90% (no condensation) at 20°C
Model	LR6	Type	Base module

Model	Trms	Rated Voltage	Mounting/Flashing	Flashing/Buzzer	Body Color	LED Unit Color	
Assembly Model: LR6	3	02	WC	N	W	RYG	
Unit Model (Body Unit): LR6	3	02	WC	N	W		
LR6 (Base)	3	02	24V DC	N	No Flashing / Buzzer	W	Off-white

WC Direct Mount / M12 Connector LED Color: R (Red) / Y (Amber) / G (Green) (From top to bottom)

M12 Wiring Connection
 Attach the M12 Connector cable to the Male Unit.

M12 Connector Pin Layout

How to Install

MOO Nut
1/2" NPT Internal Thread

Installation Figure (1/2" NPT Installation Figure)

While holding part 'A', install the 1/2" NPT Connector Cable (Optional Part) for wiring.

Recommended Torque: 2.25 Nm