


154490-11

TUBELED 25 | 705mm | RGB-W | IO-link

EAN: 4260556626284



Specifications

| | | | |
|---------------------------------------|---------------------------|-----------------------|---|
| Beam angle | 100° | Length | 705mm |
| Brand | LED2WORK | Light efficiency | 160lm/W |
| Certificates, quality marks, markings | CE, UKCA, ETL Listed | Light source | LED |
| Colour | RGB-W (daylight) | Luminous flux | R: 368lm G: 672lm B: 224lm |
| Colour rendering | >85 | Made in | Germany |
| Colour temperature range | 5200K - 5700K | Material | Housing: aluminium lens: safety glass |
| Connection | M8 (A-code), 4-pin | Operating temperature | -30°C to +55°C |
| Design | TUBELED 25 RGB-W IO-Link | Power (max.) | 19,2W |
| Dimensions | 705mm x 28mm x 23mm | Rated voltage | 24V DC |
| Dimmable | Ja, optioneel via IO-Link | Weight | 570g |
| Ingress protection | IP67 | Window type | White diffuse |
| LED life | >60 000h | | |

Good to know 📘

You can download the IODD files here: <https://ioddfinder.io-link.com/productvariants/search?vendorName=%22LED2WORK GmbH%22>

Make sure to download the flyer with extra features and controls in our downloadsection!

