

19-SR-42-  
80120-PP/B

## Datacenter rack | 800x1200x2000 | 42U | perforated doors | black



### Specifications

|              |   |
|--------------|---|
| 19" Uprights | 4 pieces with unit number and adjustable in depth |
|--------------|---|

|       |    |
|-------|----|
| Brand | 4K |
|-------|----|

|             |                |
|-------------|----------------|
| Cable entry | Top and bottom |
|-------------|----------------|

|                                       |                                |
|---------------------------------------|--------------------------------|
| Certificates, quality marks, markings | IEC 60297, EN61587-1, EN 60917 |
|---------------------------------------|--------------------------------|

|        |                |
|--------|----------------|
| Colour | RAL 9005 black |
|--------|----------------|

|               |  |
|---------------|--|
| Configuration | Geperforeerde deur vooraan en dubbele geperforeerde deur achteraan |
|---------------|--|

|            |                            |
|------------|----------------------------|
| Dimensions | B800mm x D1200mm x H2000mm |
|------------|----------------------------|

|              |   |
|--------------|---|
| Good to know | Earthing kit, 4 levelling feet and brush strip cable entry on the base included |
|--------------|---|

|                    |      |
|--------------------|------|
| Ingress protection | IP20 |
|--------------------|------|

|                |        |
|----------------|--------|
| Loading weight | 2000kg |
|----------------|--------|

|          |             |
|----------|-------------|
| Material | Sheet steel |
|----------|-------------|

|      |               |
|------|---------------|
| Type | Pre-assembled |
|------|---------------|

|        |       |
|--------|-------|
| Weight | 122kg |
|--------|-------|