

19-SR-42-
80120-G/B

Datacenter rack | 800x1200x2000 | 42U | glass
frontdoor | blind backdoor | black



Specifications

| | |
|--------------|---|
| 19" Uprights | 4 pieces with unit number and adjustable in depth |
|--------------|---|

| | |
|-------|----|
| Brand | 4K |
|-------|----|

| | |
|-------------|----------------|
| Cable entry | Top and bottom |
|-------------|----------------|

| | |
|---------------------------------------|--------------------------------|
| Certificates, quality marks, markings | IEC 60297, EN61587-1, EN 60917 |
|---------------------------------------|--------------------------------|

| | |
|--------|----------------|
| Colour | RAL 9005 black |
|--------|----------------|

| | |
|---------------|------------------------------|
| Configuration | Glass doors and blind panels |
|---------------|------------------------------|

| | |
|------------|----------------------------|
| Dimensions | B800mm x D1200mm x H2000mm |
|------------|----------------------------|

| | |
|--------------|---|
| Good to know | Earthing kit, 4 levelling feet and brush strip cable entry on the base included |
|--------------|---|

| | |
|--------------------|------|
| Ingress protection | IP20 |
|--------------------|------|

| | |
|----------------|--------|
| Loading weight | 2000kg |
|----------------|--------|

| | |
|----------|-------------|
| Material | Sheet steel |
|----------|-------------|

| | |
|------|---------------|
| Type | Pre-assembled |
|------|---------------|

| | |
|--------|-------|
| Weight | 122kg |
|--------|-------|