

LR6-  
02WCNW

## Unité de base LR6 | montage M30 | M12 | Ø60mm | blanc cassé



### Caractéristiques

Couleur boîtier	Blanc cassé	Modèle	LR6
Dimensions	Ø60mm	Montage sur poteau	Non
Direction de montage	Verticale	Raccordement	Montage direct/connecteurs M12
Humidité relative	Moins de 90% (sans condensation) à 20°C	Température d'utilisation	-20°C jusqu'à +50°C
Indice IP	IP65	Tension nominale	24V DC
Marque	Patlite	Type	Module de base

Model	Trms	Rated Voltage	Mounting/Flring	Flashing/Buzzer	Body Color	LED Unit Color			
Assembly Model	LR6	3	02	WC	N	W	RYG		
Unit Model (Body Unit)	LR6	3	02	WC	N	W			
	LR6	3	Trms	02	REV/DC	N	No Flashing / Buzzer	W	Off-white
				WC	Direct Mount / M12 Connector				
									LED Color: R (Red) / Y (Amber) / G (Green) (From top to bottom)

**M12 Wiring Connection**

Attach the M12 Connector cable to the Main Unit

**M12 Connector Pin Layout**

**How to Install**

**Installation Figure (1/2" NPT Installation Figure)**

While holding part 'A', install the 1/2" NPT Connector Cable. Failure to comply may result in damage.

Recommended Torque: 2.25 Nm