

LR6-
02WCNW

Unité de base LR6 | montage M30 | M12 | Ø60mm | blanc cassé



Caractéristiques

Couleur boîtier	Blanc cassé	Modèle	LR6
Dimensions	Ø60mm	Montage sur poteau	Non
Direction de montage	Verticale	Raccordement	Montage direct/connecteurs M12
Humidité relative	Moins de 90% (sans condensation) à 20°C	Température d'utilisation	-20°C jusqu'à +50°C
Indice IP	IP65	Tension nominale	24V DC
Marque	Patlite	Type	Module de base

Model	Trms	Rated Voltage	Mounting/Type	Flashing/Buzzer	Body Color	LED Unit Color
Assembly Model	LR6	3	02	WC	N	W
Unit Model (Body Unit)	LR6	3	02	WC	N	W

LR6 (Base)	3 (Trms)	02 (REV/DC)	N (No Flashing / Buzzer)	W (Off-white)
WC (Direct Mount / M12 Connector)				

LED Color:
R (Red) / Y (Amber) / G (Green)
(From top to bottom)

M12 Wiring Connection

Attach the M12 Connector cable to the Main Unit

M12 Connector Pin Layout

How to Install

Installation Figure (1/2" NPT Installation Figure)

While holding part 'A', install the 1/2" NPT Connector Cable. Failure to comply may result in damage.

Recommended Torque: 2.25 Nm