



## Zubehörartikel

<b>Product-Nr.</b>	200100-04
<b>EAN:</b>	4260556621890
<b>Model:</b>	Sensor Kabel, offen/M12 Buchse 4-Polig
<b>Order number:</b>	200100-04
<b>Model:</b>	Sensor Kabel, offen/M12 Buchse 4-Polig
<b>Type:</b>	Sensor cable, PUR, black
<b>Coding:</b>	A-coded
<b>Amount:</b>	1 piece
<b>Suitable for:</b>	LED2WORK lights 24V DC, except for RGB and RGB-W
<b>Cable length:</b>	5 m (~16,4 ft.)
<b>Attachment to a luminaire:</b>	Connector socket M12, straight
<b>Cable ends:</b>	open ends, 4 wires / M12 socket, straight
<b>Number of poles:</b>	4
<b>Material:</b>	Contact carrier: plastic, TPU, BK; Coupling: metal, CuZn, nickel-plated; Seal: FPM / FKM; Contacts: metal, CuSn, gold-plated
<b>Nominal voltage:</b>	250V
<b>Current load per PIN:</b>	4000 mA
<b>Ambient temperature:</b>	-30°C -> +90 °C (-22 °F -> 194 °F)
<b>Passage resistance (ohms):</b>	< 0,005
<b>Insulation resistance (Ohm):</b>	>= 100 Mio.
<b>Protection class (mounting):</b>	IP65, IP67, IP68
<b>Cable material:</b>	PUR
<b>Handle body material:</b>	Plastic, TPU, BK
<b>Contact carrier material:</b>	Plastic, TPU, BK
<b>Cover material:</b>	Metal, CuZn, nickel-plated
<b>Sealing material:</b>	FPM / FKM
<b>Contact material:</b>	Metal, CuSn, gold-plated
<b>Standards:</b>	IEC 61076-2-101
<b>Weight (net):</b>	200 g (~7 oz)
<b>Gross weight:</b>	250 g (~9 oz)